

CONCRETE SHOULD BE REINFORCED WITH WOVEN WIRE FENCING. ADDITIONAL RODS AROUND DOORS, SCRAP RODS FREE FROM RUST MAY BE USED FOR THIS PURPOSE. RUST MAY BE REMOVED BY BRUSHING. THE ROD SHOULD BE REINFORCED WITH 3- $\frac{1}{2}$ " RODS OR THEIR EQUIVALENT IN ADDITION TO WOVEN WIRE FENCING. REINFORCEMENT OF CONCRETE FLOORS SHOULD BE DONE FROM AN OLD HEATING STOVE WILL ANSWER. GRATES MAY BE MADE OF PIPES, RODS OR OLD STOVE OR FURNACE GRATES. IF IT IS DESIRED TO HEAT WATER FOR THE BATH, THE TUB SHOULD BE REINFORCED WITH THE ROD SLAB OR THE ROD MAY BE REMOVED AND REPLACED WITH A SHALLOW V-USE A TEE CONNECTION IN PLACE OF THE ELBOW AT THE BACK OF THE FIRE BOX PERMITTING A VERTICAL SMOKE PIPE WHICH HEATS THE WATER. MOVABLE HANGERS MAY BE MADE FROM $\frac{1}{2}$ " ROUND RODS.

